



Big Blue® 500X 及 600X



推荐重工业



柴油引擎

500 X - Deutz

三缸，工业级，空冷/油冷

500 X - Perkins

四缸，工业级，水冷

600 X - Deutz

三缸，工业级，空冷

600 X - Deutz

四缸，工业级，空冷/油冷

注：引擎单独由其制造商提供质保

型号	焊接工艺	电流范围	额定输出 40°C (104°F)	发电机额定输出 40°C (104°F)	运输重量
Big Blue 500 X CC	DC, 手工焊/ TIG	55-500 A	400 A @ 36 V (14.4 kW), 100% 暂载率 450 A @ 38 V (17.1 kW), 60% 暂载率 500 A @ 30 V (15 kW), 40% 暂载率	峰值: 5500 W 持续: 4000 W, 34/17 A, 120/240 VAC, 50/60 Hz (焊接时)	907 185: 728 kg (1604 lb.) 907 187: 732 kg (1614 lb.)
Big Blue 600 X CC	DC, 手工焊/ TIG	65-600 A	500 A @ 40 V (20 kW), 100% 暂载率 550 A @ 34 V (18.7 kW), 60% 暂载率 600 A @ 30 V (18 kW), 40% 暂载率		Deutz: 769 kg (1695 lb.) Perkins: 762 kg (1680 lb.) Deutz F4L: 826 kg (1820 lb.)